

**Mazzoni-hemp ball, 100 gr.**

- ▶ practical and handy design
- ▶ the fibres come from the inside of the ball
- ▶ usable until the last gramm

Article no.	PU	PU	PU	Colour	Content:
5294	8	80		nature	100 gr.


**PTFE-Thread sealing tape, standard**

Sealant for screw-couplings

- ▶ DVGW- licensed and checked in accordance to DIN EN 751-3
- ▶ temperature resistance: -100°C to +260°C
- ▶ water-repellent, corrosion-resistant
- ▶ on bobbins à 12 m length, 0,08 mm thick

PTFE is excellent resistant to most chemicals, especially acids, bases, oils, benzine, alcohols, etc.

Article no.	PU	PU	PU	Colour	Bandwidth:
5347	10	200		white	6 mm


**PTFE-Thread sealing tape, DIN-DVGW "GRp" (for coarse thread)**

Sealing materials for threads, also approved for the application of gas connections

- ▶ DVGW-licensed, checked in accordance to DIN 751-3
- ▶ temperature resistance: -200°C to +260°C

On bobbins

Length: 12 m

Thickness: 0,10 mm

PTFE is excellent resistant to most chemicals, especially acids, bases, oils, benzine, alcohols, etc.

Article no.	PU	PU	PU	Colour	Bandwidth:	
5356	10	250		white	12 mm	
5346	10	250		white	6 mm	(NEU !)


**PTFE- thread sealing tapes "FR" (for fine thread)**

Sealing material for threads, also approved for the application of gas connections DVGW-licensed, checked in accordance to DIN 751-3.

Temperature resistance: -200°C to +260°C

On bobbins

Length: 12 m

Thickness: 0,10 mm

PTFE is excellent resistant to most chemicals, especially acids, bases, oils, benzine, alcohols, etc.

Article no.	PU	PU	PU	Colour	
5348	10	250		white	
5358	10	250		white	„FRp“ for National fine screw thread

