


## Cable Ties Polyamide 6.6 standard T50R

**T-Series in PA66 natural, Article number: 111-05013**

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Catalogue page (February 2014)



All catalogue pages

**Base Data**

|                                           |                                                                 |
|-------------------------------------------|-----------------------------------------------------------------|
| Application Tool                          | MK3SP, MK3PNSP2, MK7P, EVO7, MK7HT, MK20, MK6, MK9, MK9HT, MK21 |
| Colour                                    | Natural (NA)                                                    |
| Fixation Method (FF)                      | None                                                            |
| Identification Plate Position             | none                                                            |
| Manufacturer Short Description calculated | T50R PA66 NA 100                                                |
| Product Family                            | T-Series in PA66 natural                                        |
| Product Group                             | Cable Ties Polyamide 6.6 standard                               |
| Releasable Closure (Yes/No)               | No                                                              |
| Tie Closure                               | plastic pawl                                                    |
| Type                                      | T50R.NN3P                                                       |
| Variant                                   | Inside Serrated                                                 |

**Product Dimensions**

|                             |         |
|-----------------------------|---------|
| Bundle Ø max.               | 50.0 mm |
| Bundle Ø max. (imperial)    | 1.97 "  |
| Bundle Ø min.               | 1.5 mm  |
| Bundle Ø min. (imperial)    | .06 "   |
| Length (L)                  | 200 mm  |
| Length (L) (imperial)       | 7.9 "   |
| Min. Tensile Strength (lbs) | 50 lbs  |
| Min.Tensile Strength (N)    | 225 N   |
| Width (W)                   | 4.6 mm  |
| Width (W) (imperial)        | .18 "   |

**Logistic and Packaging**

|                        |               |
|------------------------|---------------|
| Carton Quantity        | 6000 pcs.     |
| EAN / GTIN             | 5022660018961 |
| Pack Cont.             | 100           |
| Quantity of Europallet | 140000 pcs.   |
| Quantity per           | Bag           |
| Weight                 | 1.3 kg        |

**Material and Specifications**

|                               |                                    |
|-------------------------------|------------------------------------|
| ELV compliant Dir. Art. 4 (2) | YES                                |
| Flammability                  | UL94 V2                            |
| Halogenfree                   | Yes                                |
| Material                      | PA66                               |
| Material                      | Polyamide 6.6 (PA66)               |
| Operating Temperature         | -40 °C to +85 °C, (+105 °C, 500 h) |

|                               |                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------|
| REACH compliant Regu. Art. 33 | YES                                                                                                 |
| Specification                 | UL ZODZ2.E64963, DIN 30015955, GL 87 847-88 HH, GL 86 137-81 HH, BV 03856/H0 BV, Det Norske Veritas |