

Installation- and sealing material

Other pipe-mounting- and sealing material

06.5

OHA®-Tap grease for fittings

Transparent high temperature grease, good chemical resistant for the lubrication of sliding parts for hot and cold water, reduction of friction and abrasion at high temperatures and loads, protection against corrosion. Lubricant for rubber O-rings made of mineral oil compatible quality.

Working temperature -15 °C to +180 °C.

Not suitable for the food sector !

Article no.	PU	PU	PU	Colour	Content:
5304	100			colourless	7 ml tube
5312	60			colourless	25 ml tube
5314	30			colourless	200 g box



OHA®-Special tap grease for O-rings

Silicone grease. Resistant to hot and cold water, strongly adhesive and sealing, good rubber and plastic compatible. Service temperature - 40°C to +200°C.

For the slipping of stuffing boxes, O-rings, valves- and slide sealings.

The grease is conform with the KTW- recommendation of the German Health Authority in the sealing sector D1 and D2.

Article no.	PU	PU	PU	Colour	Content:
5371	100			colourless	7 ml tube
5370	60			colourless	25 ml tube
5372	1			colourless	200 g box



OHA®-Pipe joint lubricants

For plastic pipes with connecting sleeves.

The quality is conform with the KTW-recommendation of the German Health Authority.

Article no.	PU	PU	PU	Colour	Content:
5360	50			blue	150 ml tube
5361	50			blue	250 ml tube
5362	24			blue	500 ml tube
5363	12			blue	1000 ml tube
5364	20			blue	500 ml bottle



Aqua-Fermit®

Putty and cement for bushings for the sealing of wash- and WC-basins and for drains.

Article no.	PU	PU	PU	Colour	Content:
5327	30			red	1/2 kg-box

