

## Design features

- According to EN 545
- Max. operating pressure MOP (PN) 16
- Made of ductile iron, epoxy powder coated
- Flange size according to EN 1092-2 | PN 16
- Standard drilling to EN 1092-2 | PN 10

**DN**

50 - 300

## Double flanged pipe

FF-piece

**No. 8500**



## Design features

- According to EN 545
- Max. operating pressure MOP (PN) 16
- Made of ductile iron, epoxy powder coated
- Flange size according to EN 1092-2 | PN 16
- Standard drilling to EN 1092-2 | PN 10

**DN**

50 - 500

## Double flanged taper

FFR-piece

**No. 8550**



## Design features

- According to EN 545
- Max. operating pressure MOP (PN) 16
- Made of ductile iron, epoxy powder coated
- Flange size according to EN 1092-2 | PN 16
- Standard drilling to EN 1092-2 | PN 10

**DN**

50 - 400

## Double flanged elbows 45°

FFK-piece 45°

**No. 8540**



## Design features

- According to EN 545
- Max. operating pressure MOP (PN) 16
- Made of ductile iron, epoxy powder coated
- Flange size according to EN 1092-2 | PN 16
- Standard drilling to EN 1092-2 | PN 10

**DN**

50 - 500

## Double flanged elbows 90°

90° Q-piece

**No. 8530**



**E. Hawle Armaturenwerke GmbH** 4840 Vöcklabruck - Austria - Wagrainstraße 13  
Tel.: +43 (0) 7672 72576 0 - Fax: +43 (0) 7672 78464 - E-Mail: hawle@hawle.at - www.hawle.com

**F 2/1**