
Item number: 2500.55.77

Complete gullies, socket inclination: 90°

Product information for the product group



- Gully bodies DN 50
- Made of plastic (Polypropylen)
- Tested to DIN EN 1253-1
- With bracket/connecting rim
- With removable foul air trap



- Water trap depth: 50 mm
- With integrated seal to seal the flow gap between gully body and top section
- With plastic top section
 - □ Frame dimensions: 150 x 150 mm

ACO Product benefits

- Retrofit clamping flange
- Optimum cleaning option
- Adjustable height thin bed seal
- Retrofit fire protection

Fire protection



Fire resistance class R30 – R120 tested according AbZ: Z-19.17-1887

- Slot grating made from stainless steel
 - □ Load class: K 3
 - □ Slot width: 8 mm
- With protective cover added during installation

Item Technical Data 2500.55.77

Nominal width	Version	Side inlet	Recess	Flow rate	Height- adjustability	Weight
			[mm]	[l/s]	[mm]	[kg]
DN 50	Standard	Without lateral inlet	200 x 200	1.5	15 – 96	0.9

Accessories

Description	Weight	PU	Item number
	[kg]	[piece]	
Thin-bed flange Flange made of plastic with sprayed on non-woven material Suitable for holding liquid seals applied on site using the thin bed method	0.2	4	679945
Extension Made of plastic Suitable for taking plastic top sections and clamping flanges With lip seal For deeper installation of floor gullies	0.3		2040.00.00



Excluding errors and changes

Note: Top sections with slot widths ≤ 8 mm are suitable for barefoot areas.

For more information please visit: https://www.buildingdrainage.aco/products

Item number: 2500.55.77 Version: 19.06.2020 Page 1 of 2

	Description	Weight [kg]	PU [piece]	Item number
	Thin-bed flange	0.2	[biece]	2040.00.01
	Plastic flange with sprayed-on fleeceSuitable for taking liquid sealants added on-site using thin bed process			

You can find further accessories under → https://www.buildingdrainage.aco/suche/?q=2500.55.77



Note: Top sections with slot widths ≤ 8 mm are suitable for barefoot areas.