

DCE-X 6/8 Premium

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238158

Enjoy hot water on demand at any time Call up precise information at any time **Make way for efficiency** First thing in the morning, throughout the day or late at night: water is always available at the right temperature, whenever you need it. That's the assurance and precision you get with this compact instantaneous water heater. This is made possible by the memory function: two buttons, which you can use to quickly and easily save frequently used temperatures.



The main features

Fully electronically controlled compact instantaneous water heater

Maximum energy efficiency and accurate temperature delivery at all times thanks to 4i technology

Easy operation via large, illuminated multifunction display

Power saving mode due to optional ECO function

High grade design

Two temperature memory buttons for quick temperature selection

Temperature limit can be fixed at 43 °C, 50 °C or 55 °C

Exceptionally slimline, compact design



DCE-X 10/12 Premium

Product-No.: 238159



| Type | DCE-X 6/8 Premium | DCE-X 10/12 Premium |
|----------|-------------------|---------------------|
| Part no. | 238158 | 238159 |

Technical data

| | | |
|-------------------|-------------|--------------|
| Rated voltage | 220 V | 220 V |
| Rated voltage 1 | 220 V | 220 V |
| Rated voltage 2 | 230 V | 230 V |
| Rated voltage 3 | 240 V | 240 V |
| Rated output | 6.0/8.0 kW | 10.0/12.0 kW |
| Rated output 1 | 6.0/8.0 kW | 10.0/12.0 kW |
| Rated output 2 | 6.6/8.7 kW | 11.0/13.1 kW |
| Rated output 3 | 7.2/9.6 kW | 12.0/14.3 kW |
| Rated current | 27.3/36.4 A | 45.5/54.5 A |
| Rated current 1 | 27.3/36.4 A | 45.5/54.5 A |
| Rated current 2 | 28.5/38.0 A | 47.8/57.0 A |
| Rated current 3 | 30.0/40.0 A | 50.0/59.5 A |
| Fuse protection | 30/40 A | 50/60 A |
| Fuse protection 1 | 30/40 A | 50/60 A |
| Fuse protection 2 | 30/40 A | 50/60 A |
| Fuse protection 3 | 30/40 A | 50/60 A |
| Frequency | 50/60 Hz | 50/60 Hz |
| Frequency 1 | 50/60 Hz | 50/60 Hz |
| Frequency 2 | 50/60 Hz | 50/60 Hz |
| Frequency 3 | 50/60 Hz | 50/60 Hz |

| | | |
|---------------------------------|------------------|------------------|
| Phases | 1/N/PE | 1/N/PE |
| Resistivity $\rho_{15} \geq$ | 1100 Ω cm | 1100 Ω cm |
| Conductivity $\sigma_{15} \leq$ | 910 $\mu S/cm$ | 910 $\mu S/cm$ |
| IP rating | IP 25 | IP 25 |
| Temperature setting | Ki, 20–60 °C | Ki, 20–60 °C |
| Colour | white | white |
| ON | 1.3 l/min | 1.3 l/min |
| Height | 372 mm | 372 mm |
| Width | 217 mm | 217 mm |
| Depth | 109 mm | 109 mm |
| Weight | 2.50 kg | 2.50 kg |
| Energy efficiency class | A | A |

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.