



PA2210CE08 Air curtain

Electrical heat 8kW, L=1m

Item number: 19422



Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances.

The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation

Type of installation	Horizontal
Recommended installation height	2.2 m

Nominal data

Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C

Dimensions and weights

Length	1,050 mm
Height	210 mm
Depth	345 mm
Weight	19 kg

Air flow			
Air flow	900; 1200; 1000	m³/h	
Sound data			
Sound pressure (LpA)	51; 47; 42	dB(A)	
Conditions sound pressure	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m².		
Sound power (LWA)	67	dB(A)	
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.		
Motor/control supply			
Control/motor supply	230	V	
Control/motor current	0.45	A	
Input power (P1), motor	110	W	
Electric heat			
Heat output	8; 5	kW	
Heat amperage	11.5; 7.2	A	
Heat voltage	400	V	
Phases	3N~		
Temperature rise, maximum heat output, highest airflow	20	°C	
Temperature rise, maximum heat output, lowest airflow	27	°C	

Performance

Parameter	
Output	8.00 kW
Air flow	1,200 m³/h
Inlet air temperature	20 °C
Outlet air temperature	40 °C
Inlet air humidity	70.0 % r.H
Outlet air humidity	22.2 % r.H

Accessories

- PA2DR Remote + door contact (15662)
- PA2PF15 Pendulum brackets (19415)
- PAMLK PC board alarm (18690)
- PA2P15 Pendulum bar (19568)
- PA34TR15 Threaded bars (18056)

Documents

- Catalogue pages PA2200C
- Manual PA2200C
- Declaration of Conformity PA2200C
- UKCA Declaration PA2200C
- WIRING DIAGRAM PA2200C.PDF

Specification

Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m
- Horizontal mounting

Application

The PA2200C is a compact air curtain, suitable for most small entrances. The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

PA2200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

Design

With its timeless design PA2200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.