


OHA®-Spezial flange gaskets

Temperature resistant until approx. 360°C.

Huge adaptation, extremely high compressive stability, safe handling due to the high flexibility of the gasket.

Flange gaskets manufactured in accordance to DIN 2690, 2 mm thick, yellow.




Article no.	PU	PU	PU	Colour	DN:	PN:	Dimensions: mm
8028	10			yellow	10	10/16/40	18 x 45
8029	10			yellow	15	10/16/40	22 x 50
8030	10			yellow	20	10/16/40	28 x 60
8031	10			yellow	25	10/16/40	35 x 70
8032	10			yellow	32	10/16/40	43 x 82
8033	10			yellow	40	10/16/40	49 x 92
8034	10			yellow	50	10/16/40	61 x 107
8035	10			yellow	65	10/16/40	77 x 127
8036	10			yellow	80	10/16/40	90 x 142
8037	10			yellow	100	16	115 x 162
8038	5			yellow	125	16	141 x 192
8039	5			yellow	150	16	169 x 218
8041	5			yellow	200	16	220 x 273
8042	5			yellow	250	10	274 x 328

OHA®-Spezial flange gaskets

Temperature resistant until 360°C.

Huge adaption, extremely high compressive stability, safe handling due to the high flexibility of the gasket.

Flange gaskets manufactured in accordance to DIN 2631, 2 mm thick, yellow



Article no.	PU	PU	PU	Colour	DN:	PN:	Dimensions: mm
8047	10			yellow	15	6	15 x 40
8048	10			yellow	20	6	20 x 50
8049	10			yellow	25	6	25 x 60
8050	10			yellow	32	6	32 x 70
8051	10			yellow	40	6	40 x 80
8052	10			yellow	50	6	50 x 90
8053	10			yellow	65	6	65 x 110
8054	10			yellow	80	6	80 x 128
8055	10			yellow	100	6	100 x 148
8056	5			yellow	125	6	125 x 178
8057	5			yellow	150	6	150 x 202